

File Upload & Storage

Multer Configuration

Local Storage (temporary):

```
// config/multer.js
const storage = multer.diskStorage({
  destination: (req, file, cb) => {
    cb(null, req.tempFolder); // Dynamic temp folder
  },
  filename: (req, file, cb) => {
    cb(null, `${Date.now()}-${file.originalName}`);
  }
});
```

Minio Object Storage

Configuration (`config/minio.js`):

```
const minioClient = new Minio.Client({
  endPoint: process.env.MINIO_ENDPOINT,
  port: parseInt(process.env.MINIO_PORT),
  useSSL: process.env.MINIO_USE_SSL === 'true',
  accessKey: process.env.MINIO_ACCESS_KEY,
  secretKey: process.env.MINIO_SECRET_KEY
});
```

Upload Flow:

1. File uploaded to temp directory via Multer
2. Image processed/compressed with Sharp
3. File uploaded to Minio
4. Temp file deleted
5. Minio URL stored in database

Image Processing

```
const sharp = require('sharp');

// Compress and resize
await sharp(inputPath)
  .resize(800, 800, { fit: 'inside' })
  .jpeg({ quality: 80 })
  .toFile(outputPath);
```

Revision #1

Created 24 February 2026 09:29:18 by ondelivelooper

Updated 24 February 2026 09:29:33 by ondelivelooper