

ONDELIVERY

- [API PICKUP OR CASHLESS](#)

API PICKUP OR CASHLESS

Update notes

2024-07-29: Update error payload for 200 (OK): Some mandatory fields are empty

Endpoint

Endpoint	Method	Authentication
http://apiv2.jne.co.id:10102/pickupcashless	POST	<ul style="list-style-type: none">no (test environment)

Authentication

Type	Token source	Server

Header

Parameter	Value
Content-Type	application/x-www-form-urlencoded
Accept	application/json

payload type: x-www-form-urlencoded

Body request

```
{
  "username": "TESTAPI",
  "api_key": "25c898a9faea1a100859ecd9ef674548",
  "PICKUP_NAME": "ARYA",
  "PICKUP_DATE": "10-10-2019",
  "PICKUP_TIME": "23:30",
  "PICKUP_PIC": "TEAS",
  "PICKUP_PIC_PHONE": "+6289100000002",
  "PICKUP_ADDRESS": "JAKARTA",
```

"PICKUP_DISTRICT": "JAKARTA",
"PICKUP_CITY": "JAKARTA",
"PICKUP_SERVICE": "REG",
"PICKUP_VEHICLE": "MOTOR",
"BRANCH": "CGK000",
"CUST_ID": "10950700",
"ORDER_ID": "8810102030983216",
"SHIPPER_NAME": "ALI",
"SHIPPER_ADDR1": "JL. D.I PANJAITAN NO 43",
"SHIPPER_ADDR2": "JELUTUNG",
"SHIPPER_ADDR3": "JELUTUNG",
"SHIPPER_CITY": "JAMBI",
"SHIPPER_ZIP": "12345",
"SHIPPER_REGION": "JAMBI",
"SHIPPER_COUNTRY": "INDONESIA",
"SHIPPER_CONTACT": "ALI",
"SHIPPER_PHONE": "+6281234567890",
"RECEIVER_NAME": "ANA",
"RECEIVER_ADDR1": "JL SUTERA FERONIA PARK 7 ",
"RECEIVER_ADDR2": "NO 28",
"RECEIVER_ADDR3": "TANGERANG SELATAN",
"RECEIVER_CITY": "TANGERANG SELATAN",
"RECEIVER_ZIP": "54321",
"RECEIVER_REGION": "BANTEN",
"RECEIVER_COUNTRY": "INDONESIA",
"RECEIVER_CONTACT": "ANA",
"RECEIVER_PHONE": "+6285778906781",
"ORIGIN_CODE": "CGK10000",
"DESTINATION_CODE": "BDO10000",
"SERVICE_CODE": "REG",
"WEIGHT": "1",
"QTY": "1",
"GOODS_DESC": "BARANG PECAH",
"GOODS_AMOUNT": "30000",
"INSURANCE_FLAG": "0",
"SPECIAL_INS": "TEST",
"MERCHANT_ID": "TEST",
"LAT": "1",
"LON": "1",
"TYPE": "DROP",

```

"COD_FLAG": "NO",
"COD_AMOUNT": "37000",
"AWB": "1234567890"
}

```

PARAMETER	MANDATORY	TIPE DATA	DESCRIPTION	NOTES
username			YOUR USERNAME	
api_key			YOUR API KEY	
PICKUP_NAME	Y	VARCHAR2 (50 Byte)	Fill it with the seller pickup name	
PICKUP_DATE	Y	DATE	Fill it with the pickup date (Format DD-MM-YYYY)	
PICKUP_TIME	Y	VARCHAR2 (30 Byte)	Fill it with the pickup time (Format H24:MM)	
PICKUP_PIC	Y	VARCHAR2 (30 Byte)	Fill it with the Contact name of pickup seller	
PICKUP_PIC_PHONE	Y	VARCHAR2 (30 Byte)	Fill it with the phone number of pickup seller	
PICKUP_ADDRESS	Y	VARCHAR2 (300 Byte)	Fill it with the Address name of pickup seller	
PICKUP_DISTRICT	Y	VARCHAR2 (30 Byte)	Fill it with the District name of pickup seller	
PICKUP_CITY	Y	VARCHAR2 (30 Byte)	Fill it with the City name of pickup seller	
PICKUP_SERVICE	Y	VARCHAR2 (30 Byte)	Fill it with the Service name of pickup (Value : Domestic or Intracity or All)	
PICKUP_VEHICLE	Y	VARCHAR2 (100 Byte)	Fill it with the Vehicle name of pickup (Value : Motor , Mobil or Truck)	
BRANCH	Y	VARCHAR2 (6 Byte)	Fill it with the Branch of pickup seller (for testing u can fill with CGK000)	
CUST_ID	Y	VARCHAR2 (10 Byte)	Fill it with cust id in JNE	

ORDER_ID	Y	VARCHAR2 (20 Byte)	Fill it with the unique number in every order or goods.	
SHIPPER_NAME	Y	VARCHAR(30 BYTE)	Value of this Parameter is Name of the Shipper	
SHIPPER_ADDR1	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 1 of Shipper	
SHIPPER_ADDR2	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 2 of Shipper	
SHIPPER_ADDR3		VARCHAR(85 BYTE)	Value of this Parameter is Address 3 of Shipper	
SHIPPER_CITY	Y	VARCHAR(20 BYTE)	Value of this Parameter is City of Shipper	
SHIPPER_ZIP	Y	VARCHAR(5 BYTE)	Value of this Parameter is zip of Shipper	
SHIPPER_REGION	Y	VARCHAR(20 BYTE)	Value of this Parameter is Region of Shipper	
SHIPPER_COUNTRY		VARCHAR(20 BYTE)	Value of this Parameter is Country of Shipper	
SHIPPER_CONTACT	Y	VARCHAR(20 BYTE)	Value of this Parameter is Contact Name of Shipper	
SHIPPER_PHONE	Y	VARCHAR(50 BYTE)	Value of this Parameter is Phone Number of Shipper	
RECEIVER_NAME	Y	VARCHAR(30 BYTE)	Value of this Parameter is Name of Receiver	
RECEIVER_ADDR1	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 1 of Receiver	
RECEIVER_ADDR2	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 2 of Receiver	
RECEIVER_ADDR3		VARCHAR(85 BYTE)	Value of this Parameter is Address 3 of Receiver	

RECEIVER_CITY	Y	VARCHAR(20 BYTE)	Value of this Parameter is City of Receiver	
RECEIVER_ZIP	Y	VARCHAR(5 BYTE)	Value of this Parameter is Zip Code of Receiver	
RECEIVER_REGION	Y	VARCHAR(20 BYTE)	Value of this Parameter is Region of Receiver	
RECEIVER_COUNTRY		VARCHAR(20 BYTE)	Value of this Parameter is Country of Receiver	
RECEIVER_CONTACT	Y	VARCHAR(20 BYTE)	Value of this Parameter is Contact Name of Receiver	
RECEIVER_PHONE	Y	VARCHAR(50 BYTE)	Value of this Parameter is Phone of Customer	
ORIGIN_CODE	Y	VARCHAR(10 BYTE)	Value of this Parameter is Origin Code	
DESTINATION_CODE	Y	VARCHAR(10 Byte)	Value of this Parameter is Destination Code	
SERVICE_CODE	Y	VARCHAR(10 BYTE)	Value of service code or name	
WEIGHT	Y	NUMBER(10,3)	Value of this Parameter is Weight of the goods	
QTY	Y	NUMBER(10,3)	Value of this Parameter is Qty of the goods	
GOODS_DESC	Y	VARCHAR(60 BYTE)	Value of this Parameter is the goods	
GOODS_AMOUNT	Y	NUMBER	Value of this Parameter is Amount of the goods	
INSURANCE_FLAG	Y	VARCHAR(1 BYTE)	Value of this Parameter is Flag of insurance, (Fill ?Y? if it?s insurance and fill ?N? if not.)	
SPECIAL_INS	Y	VARCHAR(60 Byte)	Value of this Parameter special instruction	

MERCHANT_ID	Y	VARCHAR(100 Byte)	Fill With the Merchant or seller id	
LAT		Varchar(60 Byte)	Fill with Lat	
LON		Varchar(60 Byte)	Fill with Lon	
TYPE	Y	Varchar(10 Byte)	Fill with DROP or PICKUP	
COD_FLAG		Varchar (3 byte)	Fill with `YES? if the order is COD and fill with `NO? if the order is not COD	
COD_AMOUNT		Number	Fill with cod amount	
AWB		Varchar (16 Byte)	Fill with our airwaybill number	
TAX_VALUE	(khusus kiriman batam)	Number	Fill with tax amount	
ITEM_TYPE	(khusus kiriman batam)	VARCHAR2 (10 Byte)	Value of this parameter is item type	1 = Eks-impor/barang dagangan, 2 = Lokal, 3 = Transit, 4 = Retur, 5 = Personal
HS_CODE	(khusus kiriman batam)	VARCHAR2 (300 Byte)	Value of this parameter is hs code, qty and the goods value.the Format (Goods Value;qty;hs_code) (and using comma delimitter if more than one hs code) and maximum is five hscore for one transaction	Example : 1000000;1;4204,200 0000;2;4905,300000 0;3;4988
NPWP	(khusus kiriman batam)	VARCHAR2 (90 Byte)	Fill with npwp number	
RETURN_NAME		VARCHAR2 (30 Byte)	Filled with Return name	
RETURN_ADDR1		VARCHAR2 (30 Byte)	Filled with Return address	
RETURN_ADDR2		VARCHAR2 (30 Byte)	Filled with Return address	
RETURN_ADDR3		VARCHAR2 (30 Byte)	Filled with Return address	
RETURN_CITY		VARCHAR2 (20 Byte)	Filled with Return city	
RETURN_ZIP		VARCHAR2 (5 Byte)	Filled with Return zip	

RETURN_REGION		VARCHAR2 (20 Byte)	Filled with Return region	
RETURN_COUNTRY		VARCHAR2 (20 Byte)	Filled with Return country	
RETURN_CONTACT		VARCHAR2 (20 Byte)	Filled with Return contact	
RETURN_PHONE		VARCHAR2 (15 Byte)	Filled with Return phone	
RETURN_BRANCH		VARCHAR2 (6 Byte)	Filled with Return branch	

Result example

200 (OK)

```
{
  "detail": [
    {
      "status": "success",
      "cnote_no": "0109401600067399"
    }
  ]
}
```

Error example

200 (OK): Duplicate order id

```
{
  "detail": [
    {
      "reason": "Order id already exist, please try another one",
      "status": "Error",
      "cnote": "1234567890"
    }
  ]
}
```

200 (OK): Some mandatory fields are empty

```
{  
  "status": false,  
  "error": "Content not confirm our security Policy."  
}
```

200 (OK): Incorrect username/API key

```
{  
  "error": "Username Or API KEY Not Found.",  
  "status": false  
}
```