ONMARKET

- GENERATE AIRWAYBILL (CREATE SHIPMENT)

GENERATE AIRWAYBILL (CREATE SHIPMENT)

Endpoint

Endpoint	Method	Authentication
http://apiv2.jne.co.id:10102/tracing/api/generatecnote	POST	• no (test environment)

Authentication

Type	Token source	Server

Header

Parameter	Value
Content-Type	application/x-www-form-urlencoded

Body request

> Type: x-www-form-urlencoded


```
{
  "username": "TESTAPI",
  "api_key": "25c898a9faea1a100859ecd9ef674548",
  "OLSHOP_BRANCH": "CGK000",
  "OLSHOP_CUST": "TESTAKUN",
  "OLSHOP_ORDERID": "20240705002",
  "OLSHOP_SHIPPER_NAME": "ALI",
  "OLSHOP_SHIPPER_ADDR1": "JAKARTA NO 44",
  "OLSHOP_SHIPPER_ADDR2": "KALIBATA",
  "OLSHOP_SHIPPER_ADDR3": "KALIBATA",
```

```
  "OLSHOP_SHIPPER_CITY": "JAKARTA",
  "OLSHOP_SHIPPER_REGION": "JAKARTA",
  "OLSHOP_SHIPPER_ZIP": "12345",
  "OLSHOP_SHIPPER_PHONE": "+6289876543212",
  "OLSHOP_RECEIVER_NAME": "ANA",
  "OLSHOP_RECEIVER_ADDR1": "BANDUNG NO 12",
  "OLSHOP_RECEIVER_ADDR2": "CIBIRU",
  "OLSHOP_RECEIVER_ADDR3": "BANDUNG",
  "OLSHOP_RECEIVER_CITY": "BANDUNG",
  "OLSHOP_RECEIVER_REGION": "JAWA BARAT",
  "OLSHOP_RECEIVER_ZIP": "12365",
  "OLSHOP_RECEIVER_PHONE": "+6285789065432",
  "OLSHOP_QTY": "1",
  "OLSHOP_WEIGHT": "1",
  "OLSHOP_GOODSDESC": "TEST",
  "OLSHOP_GOODSVALUE": "1000",
  "OLSHOP_GOODSTYPE": "1",
  "OLSHOP_INST": "TEST",
  "OLSHOP_INS_FLAG": "N",
  "OLSHOP_ORIG": "CGK10000",
  "OLSHOP_DEST": "BDO10000",
  "OLSHOP_SERVICE": "REG",
  "OLSHOP_COD_FLAG": "N",
  "OLSHOP_COD_AMOUNT": "0"
}
```


Properties	**Data type**	**Description**
username*		
api_key*		
OLSHOP_BRANCH*	VARCHAR(10 BYTE)	Value of this Parameter is Branch code
OLSHOP_CUST*	VARCHAR(10 BYTE)	Values is your Cust no
OLSHOP_ORDERID*	VARCHAR(20 BYTE)	Value of this Parameter is Order Id of the goods
OLSHOP_SHIPPER_NAME*	VARCHAR(30 BYTE)	Value of this Parameter is Name of Shipper
OLSHOP_SHIPPER_ADDR1*	VARCHAR(30 BYTE)	Value of this Parameter is Address 1 of Shipper
OLSHOP_SHIPPER_ADDR2*	VARCHAR(30 BYTE)	Value of this Parameter is Address 2 of Shipper

OLSHOP_SHIPPER_ADDR3	VARCHAR(30 BYTE)	Value of this Parameter is Address 3 of Shipper
OLSHOP_SHIPPER_CITY*	VARCHAR(20 BYTE)	Value of this Parameter is City of Shipper
OLSHOP_SHIPPER_REGION	VARCHAR(20 BYTE)	Value of this Parameter is Region of Shipper
OLSHOP_SHIPPER_ZIP*	VARCHAR(5 BYTE)	Value of this Parameter is zip of Shipper
OLSHOP_SHIPPER_PHONE*	NUMBER (15 BYTE)	Value of this Parameter is Phone of Shipper
OLSHOP_RECEIVER_NAME*	VARCHAR(30 BYTE)	Value of this Parameter is Name of Customer
OLSHOP_RECEIVER_ADDR1*	VARCHAR(30 BYTE)	Value of this Parameter is Address 1 of Customer
OLSHOP_RECEIVER_ADDR2*	VARCHAR(30 BYTE)	Value of this Parameter is Address 2 of Customer
OLSHOP_RECEIVER_ADDR3	VARCHAR(30 BYTE)	Value of this Parameter is Address 3 of Customer
OLSHOP_RECEIVER_CITY*	VARCHAR(20 BYTE)	Value of this Parameter is City of Customer
OLSHOP_RECEIVER_REGION	VARCHAR(20 BYTE)	Value of this Parameter is Region of Customer
OLSHOP_RECEIVER_ZIP*	VARCHAR(5 BYTE)	Value of this Parameter is zip of Customer
OLSHOP_RECEIVER_PHONE*	NUMBER (15 BYTE)	Value of this Parameter is Phone of Customer
OLSHOP_QTY*	NUMBER(5)	Value of this Parameter is Qty of the goods (Number)
OLSHOP_WEIGHT*	NUMBER(3)	Value of this Parameter is Weight of the goods (Number)
OLSHOP_GOODSDESC*	VARCHAR(60 BYTE)	Value of this Parameter is Description of the goods
OLSHOP_GOODSVALUE*	NUMBER(12 BYTE)	Value of this Parameter is Amount of the goods
OLSHOP_GOODSTYPE*	VARCHAR(1 BYTE)	Default value ???2??? (No quotes)
OLSHOP_INST	VARCHAR(60 BYTE)	Value of this Parameter is Instruction of the goods
OLSHOP_INS_FLAG*	VARCHAR (1 Byte)	Fill ???Y??? if insurance and fill ???N??? if not
OLSHOP_ORIG*	VARCHAR(10 BYTE)	Value of this Parameter is Origin of the resellers value is CGK10000

OLSHOP_DEST*	VARCHAR(10 BYTE)	Value of this Parameter is Destination of the goods (with Code)
OLSHOP_SERVICE*	VARCHAR(10 BYTE)	Value of this Parameter is Service of the goods (Value REG, YES, SS)
OLSHOP_COD_FLAG*	VARCHAR (3 Byte)	Fill ???YES??? if COD and fill ???N??? if not
OLSHOP_COD_AMOUNT*	NUMBER(12 BYTE)	Value of this Parameter is COD Amount of the goods

Result example

200 OK


```
{
   "detail": [
      {
         "status": "sukses",
         "cnote_no": "010116240120789"
      }
   ]
}
```


Error example

200 OK

Duplicate OLSHOP_ORDERID


```
{
   "detail": [
      {
         "status": "Error",
         "reason": "Transaction no. already exists, please try with another",
         "cnote_no": "010116240120789"
      }
```

```
    ]
}
```


200 OK

OLSHOP_ORIG does not exist


```
{
    "detail": [
        {
            "status": "Error",
            "reason": "Origin Code CGK10100 Not Exists",
            "cnote_no": null
        }
    ]
}
```


200 OK

wrong api_key value


```
{
    "error": "Username Or API KEY Not Found.",
    "status": "false"
}
```