

JNE API

API Integration for JNE

- [ONMARKET & ONDELIVERY](#)
 - [Get Tariff](#)
 - [Airwaybill Tracking](#)
- [ONMARKET](#)
 - [GENERATE AIRWAYBILL \(CREATE SHIPMENT\)](#)
- [ONDELIVERY](#)
 - [API PICKUP OR CASHLESS](#)

ONMARKET & ONDELIVERY

Get Tariff

Endpoint

Endpoint	Authentication
http://apiv2.jne.co.id:10102/tracing/api/pricedev	no

Header

Parameter	Value
Content-Type	application/x-www-form-urlencoded
Accept	application/json

Body request

payload type: x-www-form-urlencoded

```
{
  "username": "TESTAPI",
  "api_key": "25c898a9faea1a100859ecd9ef674548",
  "from": "CGK10000",
  "thru": "BDO10000",
  "weight": "1"
}
```

Parameter	Value	Desc
username	CUST_USERNAME	PROVIDED BY EMAIL
api_key	CUST_APIKEY	PROVIDED BY EMAIL
from	VARCHAR (10 Byte)	Origin Code
thru	VARCHAR (10 Byte)	Destination Code
weight	Number	Weight in kg

Result example

200 OK

```
{
  "price": [
    {
      "origin_name": "JAKARTA",
      "destination_name": "BANDUNG",
      "service_display": "REG",
      "service_code": "REG19",
      "goods_type": "Document/Paket",
      "currency": "IDR",
      "price": "12000",
      "etd_from": "1",
      "etd_thru": "2",
      "times": "D"
    },
    {
      "origin_name": "JAKARTA",
      "destination_name": "BANDUNG",
      "service_display": "JTR",
      "service_code": "JTR5",
      "goods_type": "Paket",
      "currency": "IDR",
      "price": "18000",
      "etd_from": "3",
      "etd_thru": "4",
      "times": "D"
    },
    {
      "origin_name": "JAKARTA",
      "destination_name": "BANDUNG",
      "service_display": "YES",
      "service_code": "YES19",
      "goods_type": "Document/Paket",
      "currency": "IDR",
      "price": "24000",
```

```
"etd_from": "1",
"etd_thru": "1",
"times": "D"
},
{
  "origin_name": "JAKARTA",
  "destination_name": "BANDUNG",
  "service_display": "JTR",
  "service_code": "JTR18",
  "goods_type": "Paket",
  "currency": "IDR",
  "price": "45000",
  "etd_from": "3",
  "etd_thru": "4",
  "times": "D"
},
{
  "origin_name": "JAKARTA",
  "destination_name": "BANDUNG",
  "service_display": "JTR<130",
  "service_code": "JTR<130",
  "goods_type": "Paket",
  "currency": "IDR",
  "price": "500000",
  "etd_from": null,
  "etd_thru": null,
  "times": null
},
{
  "origin_name": "JAKARTA",
  "destination_name": "BANDUNG",
  "service_display": "JTR<150",
  "service_code": "JTR<150",
  "goods_type": "Paket",
  "currency": "IDR",
  "price": "500000",
  "etd_from": null,
  "etd_thru": null,
  "times": null
}
```

```
    },
    {
      "origin_name": "JAKARTA",
      "destination_name": "BANDUNG",
      "service_display": "JTR250",
      "service_code": "JTR250",
      "goods_type": "Paket",
      "currency": "IDR",
      "price": "850000",
      "etd_from": null,
      "etd_thru": null,
      "times": null
    },
    {
      "origin_name": "JAKARTA",
      "destination_name": "BANDUNG",
      "service_display": "SPS",
      "service_code": "SPS15",
      "goods_type": "Document/Paket",
      "currency": "IDR",
      "price": "403000",
      "etd_from": null,
      "etd_thru": null,
      "times": null
    }
  ]
}
```

Error example

200 OK

```
{
  "error": "Price Not Found.",
  "status": false
}
```


Airwaybill Tracking

Endpoint

Endpoint	Method	Authentication
http://apiv2.jne.co.id:10102/tracing/api/list/v1/cnote/{AWB_VALUE}	POST	no (test)

Authentication

Type	Token source	Server

Header

Parameter	Value
Content-Type	application/x-www-form-urlencoded
Accept	application/json

Body Request

```
{
  "username": "TESTAPI",
  "api_key": "25c898a9faea1a100859ecd9ef674548"
}
```

Parameter	Description
username	CUST_USERNAME
api_key	CUST_APIKEY

NOTES

Replace {AWB_VALUE} with corresponding AWB

example:

<http://apiv2.jne.co.id:10102/tracing/api/list/v1/cnote/5403212200022724>

Result example

200 OK

```
{
  "cnote": {
    "cnote_no": "5403212200022724",
    "reference_number": null,
    "cnote_origin": "TGR10000",
    "cnote_destination": "AMI20508",
    "cnote_services_code": "REG",
    "servicetype": "REG19",
    "cnote_cust_no": "80519800",
    "cnote_date": "2022-01-09T01:26:16.000+07:00",
    "cnote_pod_receiver": "A YANI",
    "cnote_receiver_name": "AHMAD YANI YANI",
    "city_name": "MOYOHULU,SUMBAWABESAR",
    "cnote_pod_date": "2022-01-11T10:32:00.000+07:00",
    "pod_status": "DELIVERED",
    "last_status": "DELIVERED TO [A YANI | 11-01-2022 10:32 | SUMBAWA BESAR ]",
    "cust_type": "999",
    "cnote_amount": "55000",
    "cnote_weight": "1",
    "pod_code": "D01",
    "keterangan": "YANG BERSANGKUTAN",
    "cnote_goods_descr": "-",
    "freight_charge": "55000",
    "shippingcost": "55000",
    "insuranceamount": "0",
    "priceperkg": "55000",
    "signature": null,
    "photo": null,
    "long": null,
    "lat": null,
  }
}
```

```
"estimate_delivery": " Days"
},
"detail": [
  {
    "cnote_no": "5403212200022724",
    "cnote_date": "09-01-2022 01:26",
    "cnote_weight": "1",
    "cnote_origin": "TANGERANG",
    "cnote_shipper_name": "LEVI.CO.ID - LEVI&#39;S OFFICI",
    "cnote_shipper_addr1": "TAMAN TEKNO BSD BLOK D2TANGERA",
    "cnote_shipper_addr2": "NG SELATAN, SETU, SETU",
    "cnote_shipper_addr3": null,
    "cnote_shipper_city": "TANGERANG",
    "cnote_receiver_name": "AHMAD YANI YANI",
    "cnote_receiver_addr1": "SUMBAWA, MOYO HULU",
    "cnote_receiver_addr2": null,
    "cnote_receiver_addr3": null,
    "cnote_receiver_city": "MOYOHULU,SUMBAWABESA"
  }
],
"history": [
  {
    "date": "09-01-2022 01:18",
    "desc": "RECEIVED AT SORTING CENTER [TANGERANG]",
    "code": "OP1"
  },
  {
    "date": "09-01-2022 01:26",
    "desc": "SHIPMENT RECEIVED BY JNE COUNTER OFFICER AT [TANGERANG]",
    "code": "RC1"
  },
  {
    "date": "09-01-2022 04:08",
    "desc": "PROCESSED AT SORTING CENTER [TANGERANG, OTB LEGUTI]",
    "code": "OP2"
  },
  {
    "date": "09-01-2022 12:35",
    "desc": "DEPARTED FROM TRANSIT [GATEWAY , JAKARTA]",
```

```
    "code": "TP4"
  },
  {
    "date": "10-01-2022 11:14",
    "desc": "RECEIVED AT WAREHOUSE [JL AMIR HAMZAH 102 (INBOUND)]",
    "code": "IP1"
  },
  {
    "date": "11-01-2022 08:19",
    "desc": "WITH DELIVERY COURIER [MATARAM]",
    "code": "IP3"
  },
  {
    "date": "11-01-2022 10:32",
    "desc": "DELIVERED TO [A YANI | 11-01-2022 10:32 | SUMBAWA BESAR ]",
    "code": "D01"
  }
]
}
```

Error example

200 OK

AWB not found

```
{
  "error": "Cnote No. Not Found.",
  "status": false
}
```

ONMARKET

GENERATE AIRWAYBILL (CREATE SHIPMENT)

Endpoint

Endpoint	Method	Authentication
http://apiv2.jne.co.id:10102/tracing/api/generatecnote	POST	<ul style="list-style-type: none">no (test environment)

Authentication

Type	Token source	Server

Header

Parameter	Value
Content-Type	application/x-www-form-urlencoded

Body request

Type: x-www-form-urlencoded

```
{
  "username": "TESTAPI",
  "api_key": "25c898a9faea1a100859ecd9ef674548",
  "OLSHOP_BRANCH": "CGK000",
  "OLSHOP_CUST": "TESTAKUN",
  "OLSHOP_ORDERID": "20240705002",
  "OLSHOP_SHIPPER_NAME": "ALI",
  "OLSHOP_SHIPPER_ADDR1": "JAKARTA NO 44",
  "OLSHOP_SHIPPER_ADDR2": "KALIBATA",
```

```

"OLSHOP_SHIPPER_ADDR3": "KALIBATA",
"OLSHOP_SHIPPER_CITY": "JAKARTA",
"OLSHOP_SHIPPER_REGION": "JAKARTA",
"OLSHOP_SHIPPER_ZIP": "12345",
"OLSHOP_SHIPPER_PHONE": "+6289876543212",
"OLSHOP_RECEIVER_NAME": "ANA",
"OLSHOP_RECEIVER_ADDR1": "BANDUNG NO 12",
"OLSHOP_RECEIVER_ADDR2": "CIBIRU",
"OLSHOP_RECEIVER_ADDR3": "BANDUNG",
"OLSHOP_RECEIVER_CITY": "BANDUNG",
"OLSHOP_RECEIVER_REGION": "JAWA BARAT",
"OLSHOP_RECEIVER_ZIP": "12365",
"OLSHOP_RECEIVER_PHONE": "+6285789065432",
"OLSHOP_QTY": "1",
"OLSHOP_WEIGHT": "1",
"OLSHOP_GOODSDESC": "TEST",
"OLSHOP_GOODSVALUE": "1000",
"OLSHOP_GOODSTYPE": "1",
"OLSHOP_INST": "TEST",
"OLSHOP_INS_FLAG": "N",
"OLSHOP_ORIG": "CGK10000",
"OLSHOP_DEST": "BDO10000",
"OLSHOP_SERVICE": "REG",
"OLSHOP_COD_FLAG": "N",
"OLSHOP_COD_AMOUNT": "0"
}

```

Properties	Data type	Description
username*		
api_key*		
OLSHOP_BRANCH*	VARCHAR(10 BYTE)	Value of this Parameter is Branch code
OLSHOP_CUST*	VARCHAR(10 BYTE)	Values is your Cust no
OLSHOP_ORDERID*	VARCHAR(20 BYTE)	Value of this Parameter is Order Id of the goods
OLSHOP_SHIPPER_NAME*	VARCHAR(30 BYTE)	Value of this Parameter is Name of Shipper
OLSHOP_SHIPPER_ADDR1*	VARCHAR(30 BYTE)	Value of this Parameter is Address 1 of Shipper

OLSHOP_SHIPPER_ADDR2*	VARCHAR(30 BYTE)	Value of this Parameter is Address 2 of Shipper
OLSHOP_SHIPPER_ADDR3	VARCHAR(30 BYTE)	Value of this Parameter is Address 3 of Shipper
OLSHOP_SHIPPER_CITY*	VARCHAR(20 BYTE)	Value of this Parameter is City of Shipper
OLSHOP_SHIPPER_REGION	VARCHAR(20 BYTE)	Value of this Parameter is Region of Shipper
OLSHOP_SHIPPER_ZIP*	VARCHAR(5 BYTE)	Value of this Parameter is zip of Shipper
OLSHOP_SHIPPER_PHONE*	NUMBER (15 BYTE)	Value of this Parameter is Phone of Shipper
OLSHOP_RECEIVER_NAME*	VARCHAR(30 BYTE)	Value of this Parameter is Name of Customer
OLSHOP_RECEIVER_ADDR1*	VARCHAR(30 BYTE)	Value of this Parameter is Address 1 of Customer
OLSHOP_RECEIVER_ADDR2*	VARCHAR(30 BYTE)	Value of this Parameter is Address 2 of Customer
OLSHOP_RECEIVER_ADDR3	VARCHAR(30 BYTE)	Value of this Parameter is Address 3 of Customer
OLSHOP_RECEIVER_CITY*	VARCHAR(20 BYTE)	Value of this Parameter is City of Customer
OLSHOP_RECEIVER_REGION	VARCHAR(20 BYTE)	Value of this Parameter is Region of Customer
OLSHOP_RECEIVER_ZIP*	VARCHAR(5 BYTE)	Value of this Parameter is zip of Customer
OLSHOP_RECEIVER_PHONE*	NUMBER (15 BYTE)	Value of this Parameter is Phone of Customer
OLSHOP_QTY*	NUMBER(5)	Value of this Parameter is Qty of the goods (Number)
OLSHOP_WEIGHT*	NUMBER(3)	Value of this Parameter is Weight of the goods (Number)
OLSHOP_GOODSDESC*	VARCHAR(60 BYTE)	Value of this Parameter is Description of the goods
OLSHOP_GOODSVALUE*	NUMBER(12 BYTE)	Value of this Parameter is Amount of the goods
OLSHOP_GOODSTYPE*	VARCHAR(1 BYTE)	Default value ???2??? (No quotes)
OLSHOP_INST	VARCHAR(60 BYTE)	Value of this Parameter is Instruction of the goods
OLSHOP_INS_FLAG*	VARCHAR (1 Byte)	Fill ???Y??? if insurance and fill ???N??? if not

OLSHOP_ORIG*	VARCHAR(10 BYTE)	Value of this Parameter is Origin of the resellers value is CGK10000
OLSHOP_DEST*	VARCHAR(10 BYTE)	Value of this Parameter is Destination of the goods (with Code)
OLSHOP_SERVICE*	VARCHAR(10 BYTE)	Value of this Parameter is Service of the goods (Value REG, YES, SS)
OLSHOP_COD_FLAG*	VARCHAR (3 Byte)	Fill ???YES??? if COD and fill ???N??? if not
OLSHOP_COD_AMOUNT*	NUMBER(12 BYTE)	Value of this Parameter is COD Amount of the goods

Result example

200 OK

```
{
  "detail": [
    {
      "status": "sukses",
      "cnote_no": "010116240120789"
    }
  ]
}
```

Error example

200 OK

Duplicate OLSHOP_ORDERID

```
{
  "detail": [
    {
      "status": "Error",
      "reason": "Transaction no. already exists, please try with another",
    }
  ]
}
```

```
"cnote_no": "010116240120789"
  }
]
}
```

200 OK

OLSHOP_ORIG does not exist

```
{
  "detail": [
    {
      "status": "Error",
      "reason": "Origin Code CGK10100 Not Exists",
      "cnote_no": null
    }
  ]
}
```

200 OK

wrong api_key value

```
{
  "error": "Username Or API KEY Not Found.",
  "status": "false"
}
```

ONDELIVERY

API PICKUP OR CASHLESS

Update notes

2024-07-29: Update error payload for 200 (OK): Some mandatory fields are empty

Endpoint

Endpoint	Method	Authentication
http://apiv2.jne.co.id:10102/pickupcashless	POST	<ul style="list-style-type: none">no (test environment)

Authentication

Type	Token source	Server

Header

Parameter	Value
Content-Type	application/x-www-form-urlencoded
Accept	application/json

payload type: x-www-form-urlencoded

Body request

```
{
  "username": "TESTAPI",
  "api_key": "25c898a9faea1a100859ecd9ef674548",
  "PICKUP_NAME": "ARYA",
  "PICKUP_DATE": "10-10-2019",
  "PICKUP_TIME": "23:30",
  "PICKUP_PIC": "TEAS",
  "PICKUP_PIC_PHONE": "+6289100000002",
```

"PICKUP_ADDRESS": "JAKARTA",
"PICKUP_DISTRICT": "JAKARTA",
"PICKUP_CITY": "JAKARTA",
"PICKUP_SERVICE": "REG",
"PICKUP_VEHICLE": "MOTOR",
"BRANCH": "CGK000",
"CUST_ID": "10950700",
"ORDER_ID": "8810102030983216",
"SHIPPER_NAME": "ALI",
"SHIPPER_ADDR1": "JL. D.I PANJAITAN NO 43",
"SHIPPER_ADDR2": "JELUTUNG",
"SHIPPER_ADDR3": "JELUTUNG",
"SHIPPER_CITY": "JAMBI",
"SHIPPER_ZIP": "12345",
"SHIPPER_REGION": "JAMBI",
"SHIPPER_COUNTRY": "INDONESIA",
"SHIPPER_CONTACT": "ALI",
"SHIPPER_PHONE": "+6281234567890",
"RECEIVER_NAME": "ANA",
"RECEIVER_ADDR1": "JL SUTERA FERONIA PARK 7 ",
"RECEIVER_ADDR2": "NO 28",
"RECEIVER_ADDR3": "TANGERANG SELATAN",
"RECEIVER_CITY": "TANGERANG SELATAN",
"RECEIVER_ZIP": "54321",
"RECEIVER_REGION": "BANTEN",
"RECEIVER_COUNTRY": "INDONESIA",
"RECEIVER_CONTACT": "ANA",
"RECEIVER_PHONE": "+6285778906781",
"ORIGIN_CODE": "CGK10000",
"DESTINATION_CODE": "BDO10000",
"SERVICE_CODE": "REG",
"WEIGHT": "1",
"QTY": "1",
"GOODS_DESC": "BARANG PECAH",
"GOODS_AMOUNT": "30000",
"INSURANCE_FLAG": "0",
"SPECIAL_INS": "TEST",
"MERCHANT_ID": "TEST",
"LAT": "1",
"LON": "1",

```

"TYPE": "DROP",
"COD_FLAG": "NO",
"COD_AMOUNT": "37000",
"AWB": "1234567890"
}

```

PARAMETER	MANDATORY	TIPE DATA	DESCRIPTION	NOTES
username			YOUR USERNAME	
api_key			YOUR API KEY	
PICKUP_NAME	Y	VARCHAR2 (50 Byte)	Fill it with the seller pickup name	
PICKUP_DATE	Y	DATE	Fill it with the pickup date (Format DD-MM-YYYY)	
PICKUP_TIME	Y	VARCHAR2 (30 Byte)	Fill it with the pickup time (Format H24:MM)	
PICKUP_PIC	Y	VARCHAR2 (30 Byte)	Fill it with the Contact name of pickup seller	
PICKUP_PIC_PHONE	Y	VARCHAR2 (30 Byte)	Fill it with the phone number of pickup seller	
PICKUP_ADDRESS	Y	VARCHAR2 (300 Byte)	Fill it with the Address name of pickup seller	
PICKUP_DISTRICT	Y	VARCHAR2 (30 Byte)	Fill it with the District name of pickup seller	
PICKUP_CITY	Y	VARCHAR2 (30 Byte)	Fill it with the City name of pickup seller	
PICKUP_SERVICE	Y	VARCHAR2 (30 Byte)	Fill it with the Service name of pickup (Value : Domestic or Intracity or All)	
PICKUP_VEHICLE	Y	VARCHAR2 (100 Byte)	Fill it with the Vehicle name of pickup (Value : Motor , Mobil or Truck)	
BRANCH	Y	VARCHAR2 (6 Byte)	Fill it with the Branch of pickup seller (for testing u can fill with CGK000)	
CUST_ID	Y	VARCHAR2 (10 Byte)	Fill it with cust id in JNE	

ORDER_ID	Y	VARCHAR2 (20 Byte)	Fill it with the unique number in every order or goods.	
SHIPPER_NAME	Y	VARCHAR(30 BYTE)	Value of this Parameter is Name of the Shipper	
SHIPPER_ADDR1	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 1 of Shipper	
SHIPPER_ADDR2	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 2 of Shipper	
SHIPPER_ADDR3		VARCHAR(85 BYTE)	Value of this Parameter is Address 3 of Shipper	
SHIPPER_CITY	Y	VARCHAR(20 BYTE)	Value of this Parameter is City of Shipper	
SHIPPER_ZIP	Y	VARCHAR(5 BYTE)	Value of this Parameter is zip of Shipper	
SHIPPER_REGION	Y	VARCHAR(20 BYTE)	Value of this Parameter is Region of Shipper	
SHIPPER_COUNTRY		VARCHAR(20 BYTE)	Value of this Parameter is Country of Shipper	
SHIPPER_CONTACT	Y	VARCHAR(20 BYTE)	Value of this Parameter is Contact Name of Shipper	
SHIPPER_PHONE	Y	VARCHAR(50 BYTE)	Value of this Parameter is Phone Number of Shipper	
RECEIVER_NAME	Y	VARCHAR(30 BYTE)	Value of this Parameter is Name of Receiver	
RECEIVER_ADDR1	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 1 of Receiver	
RECEIVER_ADDR2	Y	VARCHAR(85 BYTE)	Value of this Parameter is Address 2 of Receiver	
RECEIVER_ADDR3		VARCHAR(85 BYTE)	Value of this Parameter is Address 3 of Receiver	

RECEIVER_CITY	Y	VARCHAR(20 BYTE)	Value of this Parameter is City of Receiver	
RECEIVER_ZIP	Y	VARCHAR(5 BYTE)	Value of this Parameter is Zip Code of Receiver	
RECEIVER_REGION	Y	VARCHAR(20 BYTE)	Value of this Parameter is Region of Receiver	
RECEIVER_COUNTRY		VARCHAR(20 BYTE)	Value of this Parameter is Country of Receiver	
RECEIVER_CONTACT	Y	VARCHAR(20 BYTE)	Value of this Parameter is Contact Name of Receiver	
RECEIVER_PHONE	Y	VARCHAR(50 BYTE)	Value of this Parameter is Phone of Customer	
ORIGIN_CODE	Y	VARCHAR(10 BYTE)	Value of this Parameter is Origin Code	
DESTINATION_CODE	Y	VARCHAR(10 Byte)	Value of this Parameter is Destination Code	
SERVICE_CODE	Y	VARCHAR(10 BYTE)	Value of service code or name	
WEIGHT	Y	NUMBER(10,3)	Value of this Parameter is Weight of the goods	
QTY	Y	NUMBER(10,3)	Value of this Parameter is Qty of the goods	
GOODS_DESC	Y	VARCHAR(60 BYTE)	Value of this Parameter is the goods	
GOODS_AMOUNT	Y	NUMBER	Value of this Parameter is Amount of the goods	
INSURANCE_FLAG	Y	VARCHAR(1 BYTE)	Value of this Parameter is Flag of insurance, (Fill ?Y? if it?s insurance and fill ?N? if not.)	
SPECIAL_INS	Y	VARCHAR(60 Byte)	Value of this Parameter special instruction	

MERCHANT_ID	Y	VARCHAR(100 Byte)	Fill With the Merchant or seller id	
LAT		Varchar(60 Byte)	Fill with Lat	
LON		Varchar(60 Byte)	Fill with Lon	
TYPE	Y	Varchar(10 Byte)	Fill with DROP or PICKUP	
COD_FLAG		Varchar (3 byte)	Fill with `YES? if the order is COD and fill with `NO? if the order is not COD	
COD_AMOUNT		Number	Fill with cod amount	
AWB		Varchar (16 Byte)	Fill with our airwaybill number	
TAX_VALUE	(khusus kiriman batam)	Number	Fill with tax amount	
ITEM_TYPE	(khusus kiriman batam)	VARCHAR2 (10 Byte)	Value of this parameter is item type	1 = Eks-impor/barang dagangan, 2 = Lokal, 3 = Transit, 4 = Retur, 5 = Personal
HS_CODE	(khusus kiriman batam)	VARCHAR2 (300 Byte)	Value of this parameter is hs code, qty and the goods value.the Format (Goods Value;qty;hs_code) (and using comma delimitter if more than one hs code) and maximum is five hscore for one transaction	Example : 1000000;1;4204,200 0000;2;4905,300000 0;3;4988
NPWP	(khusus kiriman batam)	VARCHAR2 (90 Byte)	Fill with npwp number	
RETURN_NAME		VARCHAR2 (30 Byte)	Filled with Return name	
RETURN_ADDR1		VARCHAR2 (30 Byte)	Filled with Return address	
RETURN_ADDR2		VARCHAR2 (30 Byte)	Filled with Return address	
RETURN_ADDR3		VARCHAR2 (30 Byte)	Filled with Return address	
RETURN_CITY		VARCHAR2 (20 Byte)	Filled with Return city	
RETURN_ZIP		VARCHAR2 (5 Byte)	Filled with Return zip	

RETURN_REGION		VARCHAR2 (20 Byte)	Filled with Return region	
RETURN_COUNTRY		VARCHAR2 (20 Byte)	Filled with Return country	
RETURN_CONTACT		VARCHAR2 (20 Byte)	Filled with Return contact	
RETURN_PHONE		VARCHAR2 (15 Byte)	Filled with Return phone	
RETURN_BRANCH		VARCHAR2 (6 Byte)	Filled with Return branch	

Result example

200 (OK)

```
{
  "detail": [
    {
      "status": "success",
      "cnote_no": "0109401600067399"
    }
  ]
}
```

Error example

200 (OK): Duplicate order id

```
{
  "detail": [
    {
      "reason": "Order id already exist, please try another one",
      "status": "Error",
      "cnote": "1234567890"
    }
  ]
}
```

200 (OK): Some mandatory fields are empty

```
{  
  "status": false,  
  "error": "Content not confirm our security Policy."  
}
```

200 (OK): Incorrect username/API key

```
{  
  "error": "Username Or API KEY Not Found.",  
  "status": false  
}
```