# GENERATE AIRWAYBILL (CREATE SHIPMENT)

## Endpoint

| Endpoint | Method | Authentication |
| --- | --- | --- |
| http://apiv2.jne.co.id:10102/tracing/api/generatecnote | POST | • no (test environment) |

## Authentication

| Type | Token source | Server |
| --- | --- | --- |
| | | |

## Header

| Parameter | Value |
| --- | --- |
| Content-Type | application/x-www-form-urlencoded |

## Body request

> Type: x-www-form-urlencoded


```
{
  "username": "TESTAPI",
  "api_key": "25c898a9faea1a100859ecd9ef674548",
  "OLSHOP_BRANCH": "CGK000",
  "OLSHOP_CUST": "TESTAKUN",
  "OLSHOP_ORDERID": "20240705002",
  "OLSHOP_SHIPPER_NAME": "ALI",
  "OLSHOP_SHIPPER_ADDR1": "JAKARTA NO 44",
  "OLSHOP_SHIPPER_ADDR2": "KALIBATA",
  "OLSHOP_SHIPPER_ADDR3": "KALIBATA",
```

```
  "OLSHOP_SHIPPER_CITY": "JAKARTA",
  "OLSHOP_SHIPPER_REGION": "JAKARTA",
  "OLSHOP_SHIPPER_ZIP": "12345",
  "OLSHOP_SHIPPER_PHONE": "+6289876543212",
  "OLSHOP_RECEIVER_NAME": "ANA",
  "OLSHOP_RECEIVER_ADDR1": "BANDUNG NO 12",
  "OLSHOP_RECEIVER_ADDR2": "CIBIRU",
  "OLSHOP_RECEIVER_ADDR3": "BANDUNG",
  "OLSHOP_RECEIVER_CITY": "BANDUNG",
  "OLSHOP_RECEIVER_REGION": "JAWA BARAT",
  "OLSHOP_RECEIVER_ZIP": "12365",
  "OLSHOP_RECEIVER_PHONE": "+6285789065432",
  "OLSHOP_QTY": "1",
  "OLSHOP_WEIGHT": "1",
  "OLSHOP_GOODSDESC": "TEST",
  "OLSHOP_GOODSVALUE": "1000",
  "OLSHOP_GOODSTYPE": "1",
  "OLSHOP_INST": "TEST",
  "OLSHOP_INS_FLAG": "N",
  "OLSHOP_ORIG": "CGK10000",
  "OLSHOP_DEST": "BDO10000",
  "OLSHOP_SERVICE": "REG",
  "OLSHOP_COD_FLAG": "N",
  "OLSHOP_COD_AMOUNT": "0"
}
```


| **Properties** | **Data type** | **Description** |
|---|---|---|
| **username*** | | |
| **api_key*** | | |
| OLSHOP_BRANCH* | VARCHAR(10 BYTE) | Value of this Parameter is Branch code |
| OLSHOP_CUST* | VARCHAR(10 BYTE) | Values is your Cust no |
| OLSHOP_ORDERID* | VARCHAR(20 BYTE) | Value of this Parameter is Order Id of the goods |
| OLSHOP_SHIPPER_NAME* | VARCHAR(30 BYTE) | Value of this Parameter is Name of Shipper |
| OLSHOP_SHIPPER_ADDR1* | VARCHAR(30 BYTE) | Value of this Parameter is Address 1 of Shipper |
| OLSHOP_SHIPPER_ADDR2* | VARCHAR(30 BYTE) | Value of this Parameter is Address 2 of Shipper |

| | | |
|---|---|---|
| OLSHOP_SHIPPER_ADDR3 | VARCHAR(30 BYTE) | Value of this Parameter is Address 3 of Shipper |
| OLSHOP_SHIPPER_CITY* | VARCHAR(20 BYTE) | Value of this Parameter is City of Shipper |
| OLSHOP_SHIPPER_REGION | VARCHAR(20 BYTE) | Value of this Parameter is Region of Shipper |
| OLSHOP_SHIPPER_ZIP* | VARCHAR(5 BYTE) | Value of this Parameter is zip of Shipper |
| OLSHOP_SHIPPER_PHONE* | NUMBER (15 BYTE) | Value of this Parameter is Phone of Shipper |
| OLSHOP_RECEIVER_NAME* | VARCHAR(30 BYTE) | Value of this Parameter is Name of Customer |
| OLSHOP_RECEIVER_ADDR1* | VARCHAR(30 BYTE) | Value of this Parameter is Address 1 of Customer |
| OLSHOP_RECEIVER_ADDR2* | VARCHAR(30 BYTE) | Value of this Parameter is Address 2 of Customer |
| OLSHOP_RECEIVER_ADDR3 | VARCHAR(30 BYTE) | Value of this Parameter is Address 3 of Customer |
| OLSHOP_RECEIVER_CITY* | VARCHAR(20 BYTE) | Value of this Parameter is City of Customer |
| OLSHOP_RECEIVER_REGION | VARCHAR(20 BYTE) | Value of this Parameter is Region of Customer |
| OLSHOP_RECEIVER_ZIP* | VARCHAR(5 BYTE) | Value of this Parameter is zip of Customer |
| OLSHOP_RECEIVER_PHONE* | NUMBER (15 BYTE) | Value of this Parameter is Phone of Customer |
| OLSHOP_QTY* | NUMBER(5) | Value of this Parameter is Qty of the goods (Number) |
| OLSHOP_WEIGHT* | NUMBER(3) | Value of this Parameter is Weight of the goods (Number) |
| OLSHOP_GOODSDESC* | VARCHAR(60 BYTE) | Value of this Parameter is Description of the goods |
| OLSHOP_GOODSVALUE* | NUMBER(12 BYTE) | Value of this Parameter is Amount of the goods |
| OLSHOP_GOODSTYPE* | VARCHAR(1 BYTE) | Default value ???2??? (No quotes) |
| OLSHOP_INST | VARCHAR(60 BYTE) | Value of this Parameter is Instruction of the goods |
| OLSHOP_INS_FLAG* | VARCHAR (1 Byte) | Fill ???Y??? if insurance and fill ???N??? if not |
| OLSHOP_ORIG* | VARCHAR(10 BYTE) | Value of this Parameter is Origin of the resellers value is CGK10000 |

| | | |
|---|---|---|
| OLSHOP_DEST* | VARCHAR(10 BYTE) | Value of this Parameter is Destination of the goods (with Code) |
| OLSHOP_SERVICE* | VARCHAR(10 BYTE) | Value of this Parameter is Service of the goods (Value REG, YES, SS) |
| OLSHOP_COD_FLAG* | VARCHAR (3 Byte) | Fill ???YES??? if COD and fill ???N??? if not |
| OLSHOP_COD_AMOUNT* | NUMBER(12 BYTE) | Value of this Parameter is COD Amount of the goods |

### Result example

200 OK


```
{
   "detail": [
      {
         "status": "sukses",
         "cnote_no": "010116240120789"
      }
   ]
}
```


### Error example

200 OK

Duplicate OLSHOP_ORDERID


```
{
   "detail": [
      {
         "status": "Error",
         "reason": "Transaction no. already exists, please try with another",
         "cnote_no": "010116240120789"
      }
```

```
    ]
}
```


200 OK

OLSHOP_ORIG does not exist


```
{
    "detail": [
        {
            "status": "Error",
            "reason": "Origin Code CGK10100 Not Exists",
            "cnote_no": null
        }
    ]
}
```


200 OK

wrong api_key value


```
{
    "error": "Username Or API KEY Not Found.",
    "status": "false"
}
```



Revision #6
Created 5 July 2024 02:26:53 by ondeliveloper
Updated 17 October 2024 06:44:17 by ondeliveloper