Invoice checkout (ONDELIVERY)

Flowchart

Source:

https://cahskuy.stoplight.io/docs/OND/3c78799259e69-payment-checkout

Reference:

Transaction Flowchart

Endpoint

Endpoint	Method	Authentication
/sys/payment-checkout	POST	Yes

Authentication (Basic)

Param	Value
username	on-booking
password	iRiLiODOSV1X8WMVCThlOhpwnOYdsRYXiaJI3hIfeDZKaiOkKioUBQr1Y7PlnXhM

Body request example


```
{
   "total_amount": 40000,
   "service": "ONDELIVERY",
   "source": "XENDIT",
   "client": "usernew1",
   "waybill_number": "OND123456789",
```

```
    "xendit_methods": ["QRIS"]
}
```

No.	Properties	Properties of	Data type	Required	Description
1	total_amount		integer	yes	Total nominal amount for the invoice.
2	service		string	yes	ONINDONESIA services. Possible values: • ONDELIVERY means the source of the transaction comes from ondelivery. • ONTICKET means the source of the transaction comes from onticket. • ONMARKET means the source of the transaction comes from onmarket.

3	source		string	yes	A way that users pay for a product or service. Possible values: XENDIT or BALANCE.
4	client		string	yes	Username sender of ONDELIVERY.
5	waybill_number		string	yes	Waybill Number or AWB created from OSAS.
6	xendit_methods		array<string>	no	The specific payment channel used to pay the invoice. Possible values for bank transfer: BCA, BNI, BSI, BRI, MANDIRI, PERMATA. Possible values for ewallet: • DANA • OVO • LINKAJA • SHOPEEPAY • GCASH • GRABPAY • PAYMAYA • QRIS QRIS is only payment method for now.

Response example

200 (OK)

Example response for ONMARKET

```
{
  "xendit_invoice": "qr_dbc7200c-ed8a-4088-9430-dae9f529f6bb",
  "invoice": "OD0001N12C00006",
  "expired_at": "2024-02-14T10:02:10.065027Z",
  "amount": 40000,
  "qr_string":
"0002010102##########CO.XENDIT.WWW011893600#######14220002152#####414220010303
TTT####015CO.XENDIT.WWW021800000000000000000000TTT52045######ID5911XenditQRIS6007Jaka
rta6105121606##########3k1mOnF73h11111111#3k1mOnF73h6v53033605401163040BDB"
}
```


Properties	Properties of	Data type	Description
xendit_invoice		string	invoice ID generated by XENDIT and translated by USAPI
expired_at		timestampz	ISO date and time that the invoice expires.
invoice		string	Invoice ID generated by USAPI
qr_string		string	QR String created by XENDIT

Error response

400 Bad Request

> Some parameters may contain invalid values or some parameters are not present.


```
{
  "message": "Invalid JSON Format"
}
```


> Balance is not enough for doing transaction

```
{
  "message": "Insufficient balance"
}
```


401 Unauthorized

> Authentication header is not valid or missing


```
{
  "message": "Auth Error"
}
```


500 Internal server error

> Internal server error


```
{
  "message": "Internal server error"
}
```


Revision #13
Created 7 February 2024 08:02:37 by ondeliveloper
Updated 13 February 2024 08:52:46 by ondeliveloper