Get signature access (asymmetric signature)

Endpoint

Endpoint	Method	Server
/api/v1.0/utilities/signature-auth	POST	https://apidevportal.aspi-indonesia.or.id:44310

Header

Parameter	Value	Notes
X-TIMESTAMP	Today's date UTC+7 Example 2024-11-29T14:15:00+07:00	
X-CLIENT-KEY	Client id in Request Aplikasi Pengujian page	
Private_Key	Private key in Request Aplikasi Pengujian page	

Result example

200 OK


```
{
   "signature":
"ECMld++UIuHBE1JU8oTcpBydvL3noq19LkTur3hWuA8ptyoqGGjXQW7TrG6JgeDMLO2533rXIo3b1hjfT/CCMk4
```

vxGHDFV+YjY0r1e1mSgvYOSWhTss5DOKF0Fk3Lh0XfW5pP+6HglVGX5cluQkTB4fgTyDrJMjHZa5fttMda9S98Q
znbvtMnz"
}

Error example

400 Bad Request
X-TIMESTAMP header is not provided or value is empty

{
"responseCode": "4000000",
"responseMessage": "The timestamp field is required."
}

400 Bad Request
X-CLIENT-KEY header is not provided or value is empty

{
"responseCode": "4000000",
"responseMessage": "The clientId field is required."
}

400 Bad Request
Private_Key header is not provided or value is empty

{
"responseCode": "4000000",
"responseMessage": "The privateKey field is required."
}

Revision #2
Created 29 November 2024 08:21:48 by ondeliveloper
Updated 29 November 2024 08:49:40 by ondeliveloper